



#### **Product technical sheet**

# **ROBINIA RB1232**







2+

9 kids

22,6 m<sup>2</sup>

## **Material specification**

- ullet Construction made of Robinia very durable acacia wood with a diameter of  $\sim$  18 cm without sharp edges, resistant to weather conditions,
- Side panels made of Robinia very durable acacia wood without sharp edges, resistant to weather conditions
- Telescope made of stainless steel and durable HDPE plate, resistant to weather conditions,
- Rudder made of durable HDPE plate, resistant to weather conditions,
- Elements made of durable HPL plate, resistant to weather conditions,
- Screws covered with plastic caps and/or stainless steel screws,



#### **Facilitating disability**



easy access



integration



#### Intellectual development



manipulation



sight



## **Physical development**



balance




hiding





passage











## **Product technical sheet**

# **ROBINIA RB1232**

#### **Product data**

Length	320 cm	
Width	150 cm	
Total height	160 cm	
Age group	2+ years	
Number of users	9 kids	
Safety zone	22,6 m2	
Free fall height	110 cm	
In accordance with norm EN	orm EN 1176-1:2017	
Weight of the heaviest part	42 kg	
Dimensions of the largest part	180x18x18 cm	
Availability of spare parts	YES	
Installation time	4,5 h	

Data is subject to change without prior notice.

#### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

## **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card



VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26

M: +48 793 404 991





# Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)  Particle size from 20 to 80	Particle size from 20	30	≤200
	40	≤300	
woodchips (A,C)  Particle size from 5 to 30	30	≤200	
	40	≤300	
sand or gravel (A (1)	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		110

## **Product technical sheet**

# **ROBINIA RB1232**

# Amount of safe surface corresponding with free fall height:

HIC <60	7,4 m <sup>2</sup>
HIC 110	15,2 m²

Data is subject to change without prior notice.

