



### **ROBINIA RB2862**








1+

12 kids

26,9 m<sup>2</sup>



#### **Material specification**

- Construction made of Robinia very durable acacia wood with a diameter of ~ 14 cm without sharp edges, resistant to weather conditions,
- $\bullet$  Construction made of Robinia very durable acacia wood with a diameter of  $\sim 18$  cm without sharp edges, resistant to weather conditions,
- Platforms made of Robinia very durable acacia wood, resistant to weather conditions,
- Gutter, tanks made of stainless steel, protected from the top with transparent polycarbonate,
- Gutter barriers made of rubber, HDPE and stainless steel,
- Manipulative elements made of stainless steel and HDPE,
- Plugs for gutters and tanks made of stainless steel and plastic,
- Water Mill wheel made of stainless steel and polycarbonate,
- Pump made of stainless steel; intended for connection to the public water supply network; stimulated pumping, similar to a hand pump;
- Screws covered with plastic caps and/or stainless steel screws,



#### **Facilitating disability**



easy access



integration



Intellectual development



sensorics




thinking


M: +48 793 404 991








#### [SS] 26,9 m<sup>2</sup>





#### **Product technical sheet**

## **ROBINIA RB2862**

#### **Product data**

Length	310 cm
Width	225 cm
Total height	170 cm
Age group	1+ years
Number of users	12 kids
Safety zone	26,9 m2
Free fall height	95 cm
The height of the platforms	62, 95 cm
In accordance with norm EN	1176-1:2017
Weight of the heaviest part	19,5 kg
Availability of spare parts	YES

Data is subject to change without prior notice.

#### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- anchoring on flat surface, 80/70 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

#### **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

 $\label{eq:decomposition} \mbox{ Detailed information in the guarantee card }$ 



biuro@vinci-play.com

www.vinci-play.com

info@vinci-play.com



## Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)  Particle size from 20 to 80	30	≤200	
	40	≤300	
woodchips (A,C)  Particle size from 5 to 30	30	≤200	
	40	≤300	
sand or gravel (A,C)	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		95

#### **Product technical sheet**

## **ROBINIA RB2862**

# Amount of safe surface corresponding with free fall height:

HIC <60	6,5 m <sup>2</sup>
HIC 62	4,4 m²
HIC 95	16,0 m <sup>2</sup>

Data is subject to change without prior notice.

