



#### **Material specification**

- Powder galvanized and powder coated or stainless steel construction of 80 x 80 mm profile,
- Platforms and climbing walls made of durable anti-slip and waterproof HPL plate,
- Roofs and side panels made of durable HDPE plate, resistant to weather conditions,
- Slides made of stainless steel with durable HDPE side panels,
- Fireman's pole made of stainless steel,
- Moving elements made of durable HDPE plate, resistant to weather conditions,
- Durable climbing stones made of polyester resin composite with mineral fillers,
- Stainless steel bars,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps on top of the structure made of rubber or polypropylene,

#### **Product technical sheet**

# **SPACE 3402**







3 - 14 years

7 kids

21,4 m<sup>2</sup>





#### **Facilitating disability**



easy access



integration



#### Intellectual development



manipulation



thinking



#### **Physical development**



sliding



climbing









#### **Product technical sheet**

## **SPACE 3402**

#### **Product data**

| Length                         | 280 cm       |  |
|--------------------------------|--------------|--|
| Width                          | 175 cm       |  |
| Total height                   | 380 cm       |  |
| Age group                      | 3 - 14 years |  |
| Number of users                | 7 kids       |  |
| Safety zone                    | 21,4 m2      |  |
| Free fall height               | 120 cm       |  |
| The height of the platforms    | 120 cm       |  |
| slide platform height          | 120 cm       |  |
| In accordance with norm EN     | 1176-1:2017  |  |
| Weight of the heaviest part    | 26 kg        |  |
| Dimensions of the largest part | 8x8x432 cm   |  |
| Availability of spare parts    | YES          |  |
| Installation time              | 5 h          |  |
| Color options                  | <b>6</b>     |  |


Data is subject to change without prior notice.


#### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

# 630 280 HIC 100 4,6 m² 200 HIC 120 21,4 m²

[SS] 21,4 m<sup>2</sup>





#### Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural

Detailed information in the guarantee card





### Surfaces according to EN 1176-1:2017

|  | Description (mm)            | Layer thickness<br>(cm) | Maximum fall<br>heights (cm) |
|--|-----------------------------|-------------------------|------------------------------|
| Turf/ top layer of soil (A,B,C)                    | -                           | -                       | ≤100                         |
| bark (A,C)  Particle size from 20 to 80            | 30                          | ≤200                    |                              |
|  | 40                          | ≤300                    |                              |
| woodchips (A,C)  Particle size from 5 to 30        | 30                          | ≤200                    |                              |
|  | 40                          | ≤300                    |                              |
| sand or gravel (A,C)  Particle size from 0,25 to 8 | 30                          | ≤200                    |                              |
|  | 0,25 to 8                   | 40                      | ≤300                         |
| synthetic attested (A,B,C)                         | Tested according to EN 1177 |                         | 120                          |

#### **Product technical sheet**

# **SPACE 3402**

# Amount of safe surface corresponding with free fall height:

| HIC 100 | 4,6 m <sup>2</sup> |
|---------|--------------------|
| HIC 120 | 16,8 m²            |

Data is subject to change without prior notice.

